

## Wire straighteners



### Wire straightener PR 6-8 / 14 rollers

Technical parameters:

Technical data PR6-8/14-14 roller

Height 112.5 cm

Width 82 cm

Depth (at the base) 39 cm

Weight 70 kg

Diameter of the straightened wire 6 - 8 mm (or in the range from 3mm to 10mm)

Straightening rollers carburized and then heat treated

Keys for adjusting rollers included YES



### Hoop iron / flat bar / strip straightener 5x50 mm

Technical parameters:

Technical data:

Tape straightening machine up to a maximum of 50 mm x 5 mm

Height: 112.5 cm

Width: 51.5 cm

Depth (at the base): 39 cm

Weight: 50kg



### The electric PRE 6-8/14 wire straightener

Technical data:

- diameter of the straightened wire: 6 - 8 mm

- height: 112.5 cm

- width: 82 cm

- depth (at the base): 39 cm

- weight: 70 kg

- number of straightening rollers: 14 pcs

- number of guide rollers: 2 pcs

- construction includes rolling bearings 18 pcs

- power supply: 230V; 50HZ; INS.F IP 54

- speed 1400 rpm / 70 rpm

- lifting capacity of the set: approx. 53kg

- straightening rollers are carburized and then heat treated

- adjusting the rollers on the bean holes using: a wrench

# The electric PRE 6-8/14 wire straightener

The PRE 6-8 /14 wire straightener is used to straighten wire in the range from Ø2 to Ø10 mm. A straightener for Ø6 mm and Ø8 mm wires is offered as the basic one. As an option, we offer straighteners equipped with rollers for straightening other wire diameters - according to the order - it is possible to equip the machine with other driver rollers, indicated by the customer, in the diameter range from Ø2mm to Ø10mm.

The wire straightener has 14 straightening rollers and two movable upper and lower guide rollers. The device is equipped with a single-phase 0.55kW 1400 rpm motor, has a durable supporting structure made of steel and a visible panel with control elements along with an emergency stop switch.

[More photos of each machine available upon customer's request](#)